## NSN 5935-00-529-0404

Electrical Receptacle Connector Body - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-529-0404 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.625 inches **Overall Diameter:** 1.954 inches **Environmental Protection:** Thermal shock resistant and vibration resistant and shock resistant and humidity resistant **Distance From Mounting Shoulder To Front Face:** Between 0.879 inches and 0.899 inches **Mounting Facility Thickness:** Between 0.062 inches and 0.250 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** 22-78 single mating end **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Operating Tempurature Rating:** Between -55.0 degrees celsius and 125.0 degrees celsius Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.500 inches **Insert Material:** Plastic single mating end **Shell Material:** 

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

## NSN 5935-00-529-0404

Electrical Receptacle Connector Body - Page 2 of 2



## **Shell Surface Treatment Specification:**

Qq-p-416, type 2, cl 3 federal specification all treatment responses

**Shell Material Specification:** 

Qq-a-591 federal specification single material response

**Bushing Accommodation Hole Shape:** 

Round w/double flat

**Thread Series Designator:** 

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0