Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-532-2519

## **Body Style:** Straight type **Overall Length:** Between 3.340 inches and 3.360 inches **Overall Height:** 0.565 inches **Overall Width:** Between 0.240 inches and 0.260 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** Between 3.090 inches and 3.110 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate or plastic phenolic single mating end **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-c-530 federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-p-19833 military specification 1st material response or mil-m-14f military specification 1st material response or mil-m-14f military specification 2nd material response single mating end Unable To Decode: Unable to decode and unable to decode **Included Contact Quantity:**

50 single mating end single contact grouping



Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.050 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-p-19833 spec.