Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-532-2650

Body Style:
Straight shape
Overall Length:
2.540 inches
Overall Width:
0.245 inches
Unthreaded Mounting Hole Diameter:
0.078 inches
Distance Between Mounting Facility Centers:
2.400 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
2 rows of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a federal specification single material response single mating end single contact grouping
Insert Material Specification:
Mil-m-14, type sdg-f military specification 1st material response single mating end
Included Contact Quantity:
32 single mating end single contact grouping
Included Contact Type:
Hermaphrodite single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.032 gold grains, troy

Electrical Receptacle Connector - Page 2 of 2



Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.