## NSN 5935-00-534-6105

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-534-6105

**Body Style:** 

Straight shape

**Overall Length:** 

Between 3.340 inches and 3.360 inches

**Overall Height:** 

0.715 inches

Overall Width:

Between 0.240 inches and 0.260 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.110 inches and 0.130 inches

**Distance Between Mounting Facility Centers:** 

Between 3.090 inches and 3.110 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of contacts non-inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Guide pin/socket

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic diallyl phthalate single mating end or plastic phenolic single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Crimp single mating end single contact grouping

**Contact Material Specification:** 

Mil-c-6941 military specification single material response single mating end single contact grouping

**Insert Material Specification:** 

Mil-p-19833 military specification single material response single mating end or mil-m-14f military specification single material response single mating end or mil-m-14f military specification single material response single mating end

**Included Contact Quantity:** 

50 single mating end single contact grouping

**Included Contact Type:** 

Round socket single mating end single contact grouping

## NSN 5935-00-534-6105

Electrical Receptacle Connector - Page 2 of 2



S	pe	cia	l F	ea	tui	es
---	----	-----	-----	----	-----	----

Left side d-shaped socket guide rotated 90 deg, right side d-shaped socket guide rotated 90 degrees clockwise from normal

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.050 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

\_\_

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-6941 spec.