NSN 5935-00-534-7548

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-534-7548 **Body Material:** Plastic **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Top or bottom mount w/molded saddle and bushing **Overall Length:** 2.218 inches **Overall Height:** 0.585 inches **Overall Width:** 1.343 inches **Mounting Hole Diameter:** Between 0.213 inches and 0.223 inches **Body Mounting Hole Accommodation Diameter:** 1.281 inches **Mounting Hole Style:** Round, w/three mounting holes/slots **Contact Maximum Current Rating In Amps:** 5.0 **Contact Material:** Beryllium copper **Contact Surface Treatment:** Gold and nickel **Accommodated Contact Quantity:** 22 Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches **Center To Center Distance Between Outside Mounting Holes Along Width:** 1.844 inches **Polarization Type:** Contact position **Projection Length Above Mounting Surface:** 0.093 inches **Mounting Method:** Threaded stud **Mounting Type For Which Designed:** Chassis

32

Thready Qty Per Inch (tpi):

NSN 5935-00-534-7548 Plug-in Electronic Components Socket - Page 2 of 2



| Inread Size: |
|------------------------------------|
| 0.190 inches |
| Contact Position Arrangement Style |
| Concentric |
| Precious Material And Location: |
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.022 gold grains, troy |
| Precious Material: |
| Gold |
| Thread Series Designator: |
| Jnf |
| Ferminal Type And Quantity: |
| 22 solder well |
| Shelf Life: |
| N/a |
| Jnit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |

A02300