

View Online at <https://aerobasegroup.com/nsn/5935-00-539-0210>

**Body Style:**

Hood, side opening, w/clamp

**Overall Length:**

3.719 inches

**Overall Height:**

2.025 inches

**Overall Width:**

1.275 inches

**Environmental Protection:**

Salt water resistant

**Cable Entrance Diameter:**

0.625 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

750.0 single mating end single contact grouping

**Polarization Method:**

Shell

**Shell Type:**

Hood, top opening

**Connector Locking Method:**

Latch

**Connector Cable Strain Relief Method:**

Cable clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Nickel

**Insert Material Specification:**

Mil-m-14, ty sdg military specification single material response single mating end

**Shell Guide Type And Location Designator:**

A pin and d pin and 4 pin and 7 pin

**Included Contact Quantity:**

32 single mating end single contact grouping

**Included Contact Type:**

Leaf spring single mating end single contact grouping

**Special Features:**

Polarizingkeys a-d, 4-7

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.032 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.