

View Online at <https://aerobasegroup.com/nsn/5935-00-539-1192>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Electrical Insulation Feature:**

Insulated from panel

**Body Style:**

Threaded bushing mounted

**Overall Length:**

1.276 inches

**Mounting Bushing Length:**

0.276 inches

**Overall Diameter:**

0.750 inches

**Bushing Accommodation Hole Shape:**

Round

**Accommodated Finger Type:**

Three conductor, slender spherical tip single finger

**Finger Accommodation Diameter:**

0.250 inches single finger

**Finger Accommodation Length:**

1.188 inches single finger

**Bushing Thru-hole Accommodation Diameter:**

0.375 inches

**Jack Contact Arrangement Designator:**

J2-1b

**End Application:**

Helicopter, carrier based asw, sh-60f; virginia class cgn (41); ticonderoga class cg (47); usns henry j. Kaiser class tao; helicopter, search and rescue, hh-60h; sturgeon class ssn (637); computer display set, an/uyq-2 (v); missile, air intercept, sidewinder (aim-9); helicopter, uscg search and rescue, hh-60j; los angeles class ssn (688)

**Mounting Facility Type And Quantity:**

1 bushing

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.375 inches

**Criticality Code Justification:**

Feat

**Terminal Type:**

Tab, solder lug

**Special Features:**

Weapon system essential

**Material:**

Silver contact

**Material:**

Silver contact

**Precious Material And Location:**

Contact, spring and terminal surfaces silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver terminal

**Surface Treatment:**

Silver terminal

**Thread Series Designator:**

Unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A03400