

View Online at <https://aerobasegroup.com/nsn/5935-00-539-1192>

Thread Class:

2a

Thread Direction:

Right-hand

Electrical Insulation Feature:

Insulated from panel

Body Style:

Threaded bushing mounted

Overall Length:

1.276 inches

Mounting Bushing Length:

0.276 inches

Overall Diameter:

0.750 inches

Bushing Accommodation Hole Shape:

Round

Accommodated Finger Type:

Three conductor, slender spherical tip single finger

Finger Accommodation Diameter:

0.250 inches single finger

Finger Accommodation Length:

1.188 inches single finger

Bushing Thru-hole Accommodation Diameter:

0.375 inches

Jack Contact Arrangement Designator:

J2-1b

End Application:

Helicopter, carrier based asw, sh-60f; virginia class cgn (41); ticonderoga class cg (47); usns henry j. Kaiser class tao; helicopter, search and rescue, hh-60h; sturgeon class ssn (637); computer display set, an/uyq-2 (v); missile, air intercept, sidewinder (aim-9); helicopter, uscg search and rescue, hh-60j; los angeles class ssn (688)

Mounting Facility Type And Quantity:

1 bushing

Thready Qty Per Inch (tpi):

32

Thread Size:

0.375 inches

Criticality Code Justification:

Feat

Terminal Type:

Tab, solder lug

Special Features:

Weapon system essential

Material:

Silver contact

Material:

Silver contact

Precious Material And Location:

Contact, spring and terminal surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver terminal

Surface Treatment:

Silver terminal

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A03400