

View Online at <https://aerobasegroup.com/nsn/5935-00-539-1201>

Thread Class:

2a and 2a

Body Style:

Straight shape w/flange

Overall Length:

2.020 inches

Overall Height:

Between 1.719 inches and 1.781 inches

Overall Width:

Between 1.719 inches and 1.781 inches

Environmental Protection:

Pressure proof

Unthreaded Mounting Hole Diameter:

Between 0.142 inches and 0.157 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.370 inches and 1.380 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.370 inches and 1.380 inches

Distance From Mounting Shoulder To Front Face:

Between 0.812 inches and 0.843 inches

Threaded Device Type:

Coupling facility and coupling facility

Mating End Quantity:

2

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

41.0 all mating ends 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 all mating ends 1st contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and externally threaded shell

Shell Material:

Aluminum alloy

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0