Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-539-2497

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.750 inches
Overall Height:
1.625 inches
Overall Width:
1.625 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Threaded Device Type:
Hub
Mating End Quantity:
Mating End Quantity: 1
1
1 Contact Position Arrangement Style:
1 Contact Position Arrangement Style: 22-14 single mating end
1   Contact Position Arrangement Style:   22-14 single mating end   Contact Removability:
1 <b>Contact Position Arrangement Style:</b> 22-14 single mating end <b>Contact Removability:</b> Nonremovable single mating end single contact grouping
1   Contact Position Arrangement Style:   22-14 single mating end   Contact Removability:   Nonremovable single mating end single contact grouping   Contact Maximum Current Rating In Amps:
1   Contact Position Arrangement Style:   22-14 single mating end   Contact Removability:   Nonremovable single mating end single contact grouping   Contact Maximum Current Rating In Amps:   22.0 single mating end single contact grouping
1   Contact Position Arrangement Style:   22-14 single mating end   Contact Removability:   Nonremovable single mating end single contact grouping   Contact Maximum Current Rating In Amps:   22.0 single mating end single contact grouping   Contact Maximum Ac Voltage Rating In Volts:
1   Contact Position Arrangement Style:   22-14 single mating end   Contact Removability:   Nonremovable single mating end single contact grouping   Contact Maximum Current Rating In Amps:   22.0 single mating end single contact grouping   Contact Maximum Ac Voltage Rating In Volts:   500.0 single mating end single contact grouping
1Contact Position Arrangement Style:22-14 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:500.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:
1Contact Position Arrangement Style:22-14 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:500.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:700.0 single mating end single contact grouping
1Contact Position Arrangement Style:22-14 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:500.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:700.0 single mating end single contact groupingPolarization Method:
1Contact Position Arrangement Style:22-14 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:500.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:700.0 single mating end single contact groupingPolarization Method:Keyway or multiple keyway
1Contact Position Arrangement Style:22-14 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:500.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:700.0 single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:
1 Contact Position Arrangement Style: 22-14 single mating end Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 700.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 0.0
1Contact Position Arrangement Style:22-14 single mating endContact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:22.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:500.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:700.0 single mating end single contact groupingPolarization Method:Keyway or multiple keywayInsert Position In Deg:0.0Shell Type:



**Thread Length:** 0.625 inches Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.375 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 19 single mating end single contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surface silver **Precious Material:** Silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0