NSN 5935-00-539-2894

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-539-2894

Body Style:
Straight type
Overall Length:
4.050 inches
Overall Height:
0.560 inches
Overall Width:
0.375 inches
Environmental Protection:
Moisture resistant and corrosion resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
3.800 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end 1st contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold and nickel single mating end 1st contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1 military specification 1st treatment response and qq-n-290, cl 2 federal specification 2nd treatment response single
mating end 1st contact grouping
Terminal Type:
Solder well single mating end 1st contact grouping
Contact Material Specification:
Qq-c-530 federal specification single material response single mating end 1st contact grouping

Insert Material Specification:

Mil-p-19833, ty gdi-30f military specification single material response or mil-m-14, ty sdg-f military specification single material response single mating end

Included Contact Quantity:

20 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

NSN 5935-00-539-2894

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-g-45204 spec.