

View Online at https://aerobasegroup.com/nsn/5935-00-539-3382

| Thread Direction: |
|----------------------------------------------------------------|
| Right-hand |
| Overall Length: |
| 0.547 inches |
| Overall Height: |
| 0.250 inches |
| Overall Width: |
| 0.375 inches |
| Threaded Device Type: |
| Mounting bushing |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 600.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 750.0 single mating end single contact grouping |
| Connector Locking Method: |
| Bayonet latch |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 70.0 single mating end single contact grouping |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 1.000 inches |
| Insert Material: |
| Plastic single mating end |
| Shell Material: |
| Copper alloy |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round |
| Included Contact Type: |
| Coaxial socket single mating end single contact grouping |
| Thread Series Designator: |
| Un |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0