## NSN 5935-00-539-5934

Telephone Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-539-5934 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Body Style:** Right angle threaded bushing mounted short frame **Overall Length:** 1.250 inches **Overall Height:** 1.938 inches **Overall Width:** 0.750 inches **Mounting Bushing Length:** 0.375 inches **Bushing Accommodation Hole Shape:** Round **Accommodated Finger Type:** Two conductor, round tip single finger **Finger Accommodation Diameter:** 0.252 inches single finger **Finger Accommodation Length:** 1.015 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.375 inches **Jack Contact Arrangement Designator: Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): **Thread Size:** 0.375 inches **Terminal Type:** Tab, solder lug Material: Any acceptable terminal **Surface Treatment:** 

Tin terminal

**Surface Treatment:** 

Any acceptable contact

## NSN 5935-00-539-5934

Telephone Jack - Page 2 of 2



## **Test Data Document:**

81349-mil-j-641 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

| Thread Ser | ies Des | ignator: |
|------------|---------|----------|
|------------|---------|----------|

Unef

## **Specification Data:**

81349-mil-j-641 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A03400