NSN 5935-00-540-6669

Thread Class: 2a and 2b

Thread Direction:

Right-hand and right-hand

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-540-6669

Body Style:
Hood, top opening w/clamp
Overall Length:
Between 1.022 inches and 1.042 inches
Overall Height:
1.870 inches
Overall Width:
Between 0.430 inches and 0.450 inches
Cable Entrance Diameter:
0.430 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
34 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Shell Type:
Hood, top opening
Connector Locking Method:
Jackscrew-socket
Connector Cable Strain Relief Method:
Cable clamp
Thread Size:
0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end

NSN 5935-00-540-6669Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Anodize
Shell Surface Treatment Specification:
Mil-a-8625 military specification single treatment response
Insert Material Specification:
Mil-m-14, type sdg-f military specification single material response single mating end
Included Contact Quantity:
34 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.034 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-m-14 spec.