

View Online at <https://aerobasegroup.com/nsn/5935-00-540-7389>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Height:

Between 1.224 inches and 1.244 inches

Overall Width:

Between 2.708 inches and 2.728 inches

Environmental Protection:

Moisture resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.755 inches and 0.775 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 2.272 inches and 2.292 inches

Distance From Mounting Shoulder To Front Face:

Between 0.159 inches and 0.179 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Polarization Method:

Guide pin/socket

Connector Locking Method:

Screw

Thready Qty Per Inch (tpi):

24

Thread Size:

0.190 inches

Insert Material:

Plastic diallyl phthalate single mating end

Insert Material Specification:

Mil-m-14, type sgd-f military specification single material response or mil-p-19833, type gdi-30f military specification single material response single mating end

Special Features:

2 polarizing guide sockets at position 1

Test Data Document:

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28731 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.