NSN 5935-00-542-8534

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-542-8534

Thread Class: 2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
2.875 inches
Overall Diameter:
1.312 inches
Cable Entrance Diameter:
0.625 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
18-8 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
41.0 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end 1st contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end 2nd contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
18
Thread Size:
1.125 inches
Terminal Location:
Back single mating end all contact groupings

NSN 5935-00-542-8534 Electrical Plug Connector - Page 2 of 2



Conner allow	single mating end all contact groupings
	ace Treatment:
	nating end all contact groupings
Insert Materia	
Rubber single	
Ū.	ace Treatment Specification:
	eral specification single treatment response single mating end all contact groupings
Terminal Typ	
	ngle mating end all contact groupings
Shell Materia	
Aluminum allo	
Shell Surface	-
Cadmium and	chromate
Shell Surface	e Treatment Specification:
Qq-p-416, typ	pe 2, cl 3 federal specification all treatment responses
Included Cor	ntact Quantity:
7 single matin	g end 2nd contact grouping
Included Con	itact Type:
Round socket	single mating end all contact groupings
Precious Mat	erial And Location:
Contact surface	ces silver
Precious Mat	terial And Weight:
0.012 silver gr	rains, troy
Precious Mat	erial:
Silver	
Thread Serie	s Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Meas	ure:
Demilitarizati	ion:
No	
Fiig:	