Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-542-8643

## Thread Class:

2a

**Thread Direction:** 

Right-hand

## **Body Style:**

Straight shape, external coupling

### **Overall Length:**

1.938 inches

**Overall Height:** 

1.375 inches

**Overall Width:** 

1.375 inches

### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

### **Unthreaded Mounting Hole Diameter:**

### Between 0.115 inches and 0.130 inches

## Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

## Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

## Distance From Mounting Shoulder To Front Face:

Between 0.750 inches and 0.781 inches

## **Threaded Device Type:**

Coupling facility

## Mating End Quantity:

1

## **Contact Position Arrangement Style:**

18-12 single mating end

## **Contact Removability:**

Nonremovable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

22.0 single mating end single contact grouping

## Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

## Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

## **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

0.0

#### Shell Type:

Solid



### **Connector Locking Method:**

Externally threaded shell

### Thread Length:

0.625 inches

## Thready Qty Per Inch (tpi):

18

## Thread Size:

1.125 inches

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping

### Shell Material:

Aluminum alloy

### Shell Surface Treatment:

Cadmium

## Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Included Contact Quantity:** 

6 single mating end single contact grouping

## Included Contact Type:

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

## **Precious Material And Weight:**

 $0.006 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.006 \ \text{silver grains}, \ \text{troy}$ 

## **Precious Material:**

Gold and silver

# Test Data Document:

81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Thread Series Designator:

Unef

## **Specification Data:**

81349-mil-c-5015 government specification

## Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No Fiig: