

View Online at <https://aerobasegroup.com/nsn/5935-00-542-8903>

**Body Style:**

Straight shape, flush mount

**Overall Length:**

1.109 inches

**Overall Height:**

1.687 inches

**Overall Width:**

3.375 inches

**Unthreaded Mounting Hole Diameter:**

0.144 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.000 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

2.875 inches

**Distance From Mounting Shoulder To Front Face:**

0.062 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

32c2 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Polarization Method:**

Mating end

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Gold single mating end all contact groupings or silver single mating end all contact groupings

**Insert Material:**

Plastic melamine single mating end or plastic phenolic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end all contact groupings or qq-s-365 federal specification single treatment response single mating end all contact groupings

**Terminal Type:**

Solder well single mating end all contact groupings

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Included Contact Quantity:**

4 single mating end 1st contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Precious Material And Location:**

Contact surfaces gold or contact surfaces silver

**Precious Material And Weight:**

0.048 gold grains, troy or 0.048 silver grains, troy

**Precious Material:**

Gold or silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.