

View Online at <https://aerobasegroup.com/nsn/5935-00-542-9231>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.860 inches

Overall Diameter:

Between 2.497 inches and 2.506 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

36-52 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Thready Qty Per Inch (tpi):

16 and 16

Thread Size:

2.062 inches and 2.250 inches

Terminal Location:

Back single mating end single contact grouping

Insert Material:

Rubber single mating end

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Steel

Included Contact Quantity:

52 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Thread Series Designator:

Uns and un

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0