

View Online at <https://aerobasegroup.com/nsn/5935-00-543-1253>

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

0.953 inches

Overall Height:

1.328 inches

Overall Width:

1.328 inches

Environmental Protection:

Moisture resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

Between 0.115 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.062 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.062 inches

Distance From Mounting Shoulder To Front Face:

Between 0.317 inches and 0.322 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

18-53 single mating end

Contact Removability:

Removable single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0 and 95.0 and 132.0 and 232.0 and 260.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Operating Temperature Rating:

Between -65.0 degrees celsius and 175.0 degrees celsius

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

53 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.053 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

96906-ms27472 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.