

View Online at <https://aerobasegroup.com/nsn/5935-00-543-8065>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

2.500 inches

Overall Diameter:

0.875 inches

Environmental Protection:

Salt water resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Nonstd single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 single mating end single contact grouping

Contact Maximum Frequency Rating:

10000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

Thread Size:

0.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic polytetrafluoroethylene single mating end

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Insert Material Specification:

Mil-m-14077 military specification single material response single mating end

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface silver

Precious Material And Weight:

0.005 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14077 spec.