NSN 5935-00-546-4407

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-546-4407 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 2.438 inches **Overall Height:** 2.500 inches **Overall Width:** 2.500 inches **Environmental Protection:** Corrosion resistant and moisture resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.173 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.938 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.938 inches **Distance From Mounting Shoulder To Front Face:** 0.875 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 36-18 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 73.0 single mating end 3rd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 100.0

Shell Type:

Solid

NSN 5935-00-546-4407

Electrical Receptacle Connector - Page 2 of 2



| Connector Locking Method: |
|--|
| Externally threaded shell |
| Thread Length: |
| 0.625 inches |
| Thready Qty Per Inch (tpi): |
| 16 |
| Thread Size: |
| 2.500 inches |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings and silver single mating end all contact groupings |
| Terminal Type: |
| Solder well single mating end all contact groupings |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Included Contact Quantity: |
| 2 single mating end 3rd contact grouping |
| Included Contact Type: |
| Round socket single mating end all contact groupings |
| Precious Material And Location: |
| Contact surface gold and contact surface silver |
| Precious Material: |
| Gold and silver |
| Test Data Document: |
| 81349-milc5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Un |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |