

**Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 1.250 inches **Overall Diameter:** 1.072 inches **Distance From Mounting Shoulder To Front Face:** 1.234 inches **Mounting Facility Thickness:** 0.197 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 14s-2 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Hood, top opening **Connector Locking Method:** Externally threaded shell Thread Length: 0.843 inches Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.875 inches **Terminal Location:** Front single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Silver single mating end single contact grouping

NSN 5935-00-547-8219 Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-547-8219

## NSN 5935-00-547-8219

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Rubber single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
4 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0