Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-548-1240

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape threaded
Overall Length:
Between 0.885 inches and 0.905 inches
Overall Diameter:
1.510 inches
Environmental Protection:
Hermetic
Distance From Mounting Shoulder To Front Face:
Between 0.780 inches and 0.800 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
37p single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
255.0 and 220.0 and 145.0 and 95.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Metal ferrous single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber fluorosilicone class fq single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping



Solder v	vell single mating end single contact grouping
Shell M	
Metal fe	
Shell Si	urface Treatment:
Tin	
Shell Si	urface Treatment Specification:
Mil-t-107	727 military specification single treatment response
Insert N	laterial Specification:
Mil-i-230	053/9 military specification single material response single mating end
include	d Contact Quantity:
37 singl	e mating end single contact grouping
Bushing	g Accommodation Hole Shape:
Round v	v/flat
Include	d Contact Type:
Round p	oin single mating end single contact grouping
Preciou	is Material And Location:
Contact	surfaces gold
	is Material And Weight:
-	old grains, troy
	ıs Material:
Gold	
	Series Designator:
Unef	
Shelf Li	te:
N/a	M
Unit Of	Measure:
 Domilit	arization:
No	
Fiig:	
A039b0	
	(military Standard):
	204 spec.