NSN 5935-00-548-1240

Thread Class:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-548-1240

2a
Thread Direction:
Right-hand
Body Style:
Straight shape threaded
Overall Length:
Between 0.885 inches and 0.905 inches
Overall Diameter:
1.510 inches
Environmental Protection:
Hermetic
Distance From Mounting Shoulder To Front Face:
Between 0.780 inches and 0.800 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
37p single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
255.0 and 220.0 and 145.0 and 95.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Size:
1.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Metal ferrous single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber fluorosilicone class fq single mating end
Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

NSN 5935-00-548-1240

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Metal ferrous
Shell Surface Treatment:
Tin
Shell Surface Treatment Specification:
Mil-t-10727 military specification single treatment response
Insert Material Specification:
Mil-i-23053/9 military specification single material response single mating end
Included Contact Quantity:
37 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.037 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.