Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-549-2843

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.938 inches
Overall Height:
1.500 inches
Overall Width:
1.500 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.156 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.156 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20-33 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
22.0 single mating end all contact groupings
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell

# NSN 5935-00-549-2843

Electrical Receptacle Connector - Page 2 of 2



Thread Size:

1.250 inches

Terminal Location:

Back single mating end all contact groupings

## **Terminal Type:**

Solder well single mating end all contact groupings

## Shell Material:

Aluminum alloy

### **Included Contact Quantity:**

11 single mating end all contact groupings

### Included Contact Type:

Round pin single mating end all contact groupings

## **Thread Series Designator:**

Unef

Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0