

View Online at <https://aerobasegroup.com/nsn/5935-00-549-3636>

**Thread Class:**

2b

**Threaded Device Type:**

Mounting hole

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

5 single mating end

**Contact Removability:**

Nonremovable single mating end all contact groupings

**Contact Maximum Current Rating In Amps:**

10.0 single mating end 2nd contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

350.0 single mating end all contact groupings

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Snap ring

**Thread Size:**

0.164 inches

**Terminal Location:**

Back single mating end all contact groupings

**Contact Material:**

Copper alloy single mating end all contact groupings

**Contact Surface Treatment:**

Nickel single mating end all contact groupings

**Insert Material:**

Plastic phenolic single mating end

**Shell Material:**

Aluminum alloy

**Shell Material Specification:**

Qq-a-519 federal specification single material response

**Included Contact Quantity:**

3 single mating end 2nd contact grouping

**Included Contact Type:**

Round pin single mating end all contact groupings

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0