

View Online at <https://aerobasegroup.com/nsn/5935-00-549-4882>

Body Material:

Plastic

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Top or bottom mount w/molded saddle

Fabrication Method:

Molded

Overall Length:

Between 2.203 inches and 2.234 inches

Tempurature Rating:

100.0 degrees celsius

Overall Height:

Between 0.859 inches and 0.891 inches

Overall Width:

Between 0.995 inches and 1.005 inches

Mounting Hole Diameter:

0.250 inches

Body Mounting Hole Accommodation Diameter:

0.750 inches

Distance Between Mounting Facility Centers:

Between 1.120 inches and 1.130 inches

Mounting Hole Style:

Round, w/two mounting holes

Specific Equipment Accommodated:

Electron tube

Contact Maximum Current Rating In Amps:

1.0

Contact Material:

Beryllium copper

Contact Surface Treatment:

Gold

Accommodated Contact Quantity:

9

Polarization Type:

Contact position

Projection Length Above Mounting Surface:

Between 0.288 inches and 0.298 inches

Mounting Method:

Saddle and threaded hole

Mounting Type For Which Designed:

Chassis

Features Provided:

Center shield

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Contact Position Arrangement Style:

Circular

Ground Terminal Type And Quantity:

2 tab, solder lug

Contact Maximum Voltage In Volts And Current Type:

660.0 ac and 660.0 dc

Special Features:

With six terminals for mtg other components and polytetrafluoroethylene insulator plate

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.009 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Furnished Items And Quantity:

2 stud

Terminal Type And Quantity:

9 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300