

View Online at <https://aerobasegroup.com/nsn/5935-00-549-4882>

**Body Material:**

Plastic

**Thread Class:**

2b

**Thread Direction:**

Right-hand

**Body Style:**

Top or bottom mount w/molded saddle

**Fabrication Method:**

Molded

**Overall Length:**

Between 2.203 inches and 2.234 inches

**Tempurature Rating:**

100.0 degrees celsius

**Overall Height:**

Between 0.859 inches and 0.891 inches

**Overall Width:**

Between 0.995 inches and 1.005 inches

**Mounting Hole Diameter:**

0.250 inches

**Body Mounting Hole Accommodation Diameter:**

0.750 inches

**Distance Between Mounting Facility Centers:**

Between 1.120 inches and 1.130 inches

**Mounting Hole Style:**

Round, w/two mounting holes

**Specific Equipment Accommodated:**

Electron tube

**Contact Maximum Current Rating In Amps:**

1.0

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Gold

**Accommodated Contact Quantity:**

9

**Polarization Type:**

Contact position

**Projection Length Above Mounting Surface:**

Between 0.288 inches and 0.298 inches

**Mounting Method:**

Saddle and threaded hole

**Mounting Type For Which Designed:**

Chassis

**Features Provided:**

Center shield

**Thready Qty Per Inch (tpi):**

40

**Thread Size:**

0.112 inches

**Contact Position Arrangement Style:**

Circular

**Ground Terminal Type And Quantity:**

2 tab, solder lug

**Contact Maximum Voltage In Volts And Current Type:**

660.0 ac and 660.0 dc

**Special Features:**

With six terminals for mtg other components and polytetrafluoroethylene insulator plate

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.009 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Furnished Items And Quantity:**

2 stud

**Terminal Type And Quantity:**

9 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A02300