NSN 5935-00-549-8628

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-549-8628

| Body Style: |
|--|
| Straight shape |
| Overall Length: |
| 2.719 inches |
| Overall Height: |
| 1.328 inches |
| Overall Width: |
| 1.594 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.144 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 14 single mating end |
| Contact Removability: |
| Nonremovable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 10.0 single mating end all contact groupings |
| Polarization Method: |
| Mating end and contact |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Friction |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings |
| Insert Material: |
| Plastic single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end all contact groupings |
| Terminal Type: |
| Solder well single mating end all contact groupings |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| Included Contact Quantity: |

2 single mating end 1st contact grouping

NSN 5935-00-549-8628

Electrical Receptacle Connector - Page 2 of 2



| Precious Material And Location: |
|--------------------------------------|
| Contact surfaces gold |
| Precious Material And Weight: |
| 0.024 gold grains, troy |
| Precious Material: |
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-g-45204 spec.