# 279



n/nsn/5935-00-549-9279

| <b>NSN 5935-00-549-9279</b><br>Tip Jack - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/593      |
| Thread Direction:                                     |
| Right-hand  |
| Electrical Insulation Feature:                        |
| Insulated completely                                  |
| Identification Code Color:                            |
| Green   |
| Body Style:   |
| Threaded bushing mounted                              |
| Overall Length:                                       |
| 0.938 inches  |
| Mounting Bushing Length:                              |
| 0.562 inches  |
| Body Length:  |
| 0.750 inches  |
| Overall Diameter:                                     |
| 0.375 inches  |
| Bushing Accommodation Hole Shape:                     |
| Round   |
| Accommodated Finger Type:                             |
| Test prod stepped single finger                       |
| Finger Accommodation Diameter:                        |
| 0.080 inches single finger                            |
| Finger Accommodation Length:                          |
| 0.562 inches single finger                            |
| Bushing Thru-hole Accommodation Diameter:             |
| 0.219 inches  |
| Capacitance In Picofarads:                            |
| 2.0   |
| Current Rating In Amps:                               |
| 10.0  |
| Thread Size:  |

Thread Size: 0.250 inches

**Terminal Type:** 

Turret

Material:

Plastic insulator

Material:

Plastic insulator

**Precious Material And Location:** 

Contact spring gold

**Precious Material:** 

Gold

# NSN 5935-00-549-9279

Tip Jack - Page 2 of 2

Surface Treatment:

Silver and nickel spring

#### Surface Treatment:

Silver spring and nickel spring

## Thread Series Designator:

Unef

### Shelf Life:

N/a

Unit Of Measure:

--

#### Demilitarization:

No

## Fiig:

A03400

