Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-552-3608

Body Style:
Straight shape, rectangular
Overall Length:
3.969 inches
Overall Height:
0.610 inches
Overall Width:
0.875 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
3.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
32 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
800.0 single mating end single contact grouping
Polarization Method:
Shell
Shell Type:
Solid
Connector Locking Method:
Lever-pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Tab, solder lug single mating end single contact grouping
Shell Material:

Copper alloy

Electrical Receptacle Connector - Page 2 of 2



Cadmiun	1
Shell Ma	terial Specification:
Qq-b-626	6 federal specification single material response
Insert Ma	aterial Specification:
Mil-m-14	, ty sdg military specification single material response single mating e
Shell Gu	ide Type And Location Designator:
A slot an	d e slot and 5 slot and 6 slot
Included	Contact Quantity:
32 single	mating end single contact grouping
Included	I Contact Type:
Leaf spri	ng single mating end single contact grouping
Precious	Material And Location:
Contact s	surfaces gold
Precious	s Material And Weight:
0.032 go	ld grains, troy
Precious	s Material:
Gold	
Shelf Lif	e:
N/a	
Unit Of M	Measure:
Demilita	rization:
No	
Fiig:	
A039b0	
Mil-std (	military Standard):
Mil-g-452	204 spec.