

View Online at <https://aerobasegroup.com/nsn/5935-00-552-3850>

Body Style:

Single card

Overall Length:

1.781 inches

Overall Height:

0.656 inches

Overall Width:

0.328 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

Between 1.526 inches and 1.536 inches

Board Accommodated Length:

1.073 inches single board and 1.083 inches single board

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of independent contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

100.0 single mating end single contact grouping

Polarization Method:

Fixed inter-contact

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic melamine single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-14, type mme military specification single material response single mating end

Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.