Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-552-5182



Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Angle shape, w/o cable clamp

Overall Diameter:

1.000 inches

Body Angle In Deg:

90.0

Environmental Protection:

Moisture resistant and vibration resistant

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

12s-4 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

900.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

1250.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Connector Locking Method:

Internally threaded coupling nut

Distance From Centerline To Connector End:

1.750 inches

Distance From Centerline To Cable End:

1.594 inches

Thready Qty Per Inch (tpi):

24 and 20

Thread Size:

0.625 inches and 0.750 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-552-5182

Electrical Plug Connector - Page 2 of 2



Contact Material: Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Anodize **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.001 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0