Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-552-7163

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.191 inches
Overall Height:
1.094 inches
Overall Width:
1.094 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.812 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.812 inches
Distance From Mounting Shoulder To Front Face:
0.562 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
12s-3 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
22.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell

Electrical Receptacle Connector - Page 2 of 2



Thready Qty Per Inch (tpi):

20

### Thread Size:

0.750 inches

# **Terminal Location:**

Back single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

## Shell Material:

Aluminum alloy

# Included Contact Quantity:

2 single mating end single contact grouping

## Included Contact Type:

Round socket single mating end single contact grouping

## **Thread Series Designator:**

Unef

## Shelf Life:

N/a

### Unit Of Measure:

Demilitarization:

No

---

Fiig:

A039b0