# NSN 5935-00-552-7419

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-552-7419

Thread Class:
2a and 2b and 2a
Thread Direction:
Right-hand and right-hand
Body Style:
Rectangular shape
Overall Length:
2.720 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.282 inches
Overall Height:
0.800 inches
Overall Width:
0.880 inches
Unthreaded Mounting Hole Diameter:
0.112 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.468 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
50 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
56 and 56 and 56
Thread Size:
0.086 inches and 0.086 inches and 0.086 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment

Contact Surface Treatment

Gold single mating end single contact grouping

# NSN 5935-00-552-7419

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material:**

Plastic diallyl phthalate and glass fiber single mating end

# **Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

# **Insert Material Specification:**

Mil-p-19833, type gdi-30f military specification all material responses single mating end

#### **Unable To Decode:**

Unable to decode and unable to decode

#### **Included Contact Quantity:**

50 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Special Features:**

Jackscrew type-male and location-right handandjackscrew type-female and location-left hand

#### **Precious Material And Location:**

Contact surfaces gold

# **Precious Material And Weight:**

0.050 gold grains, troy

#### **Precious Material:**

Gold

# **Thread Series Designator:**

Unc and unc and unc

# Shelf Life:

N/a

#### **Unit Of Measure:**

--

# Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-g-45204 spec.