Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-553-2443

| Thread Class: |
|---|
| 2a |
| Za Thread Direction: |
| |
| Right-hand |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: 1.938 inches |
| |
| Overall Height: |
| 1.500 inches |
| Overall Width: |
| 1.500 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.120 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Height: |
| 1.156 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 1.156 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.750 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 20-27 single mating end |
| Contact Removability: |
| Removable single mating end single contact grouping |
| Contact Maximum Current Rating In Amps: |
| 22.0 single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Contact Maximum Dc Voltage Rating In Volts: |
| 700.0 single mating end single contact grouping |
| Polarization Method: |
| Keyway or multiple keyway |
| Insert Position In Deg: |
| 35.0 |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| |

NSN 5935-00-553-2443

Electrical Receptacle Connector - Page 2 of 2



Thread Size:

1.250 inches

Terminal Location:

Back single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Included Contact Quantity:

14 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0