Electrical Receptacle Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-00-553-2544

Overall Length: 1.500 inches Overall Height: 0.312 inches Overall Width: 0.750 inches Unthreaded Mounting Hole Diameter: 0.312 inches Distance Between Mounting Facility Centers: 1.188 inches Mating End Quantity: 1 Contact Maximum Current Rating In Amps:
0.312 inches Overall Width: 0.750 inches Unthreaded Mounting Hole Diameter: 0.312 inches Distance Between Mounting Facility Centers: 1.188 inches Mating End Quantity: 1
0.312 inches Overall Width: 0.750 inches Unthreaded Mounting Hole Diameter: 0.312 inches Distance Between Mounting Facility Centers: 1.188 inches Mating End Quantity: 1
0.750 inches Unthreaded Mounting Hole Diameter: 0.312 inches Distance Between Mounting Facility Centers: 1.188 inches Mating End Quantity: 1
Unthreaded Mounting Hole Diameter: 0.312 inches Distance Between Mounting Facility Centers: 1.188 inches Mating End Quantity: 1
0.312 inches Distance Between Mounting Facility Centers: 1.188 inches Mating End Quantity: 1
0.312 inches Distance Between Mounting Facility Centers: 1.188 inches Mating End Quantity: 1
1.188 inches Mating End Quantity: 1
1.188 inches Mating End Quantity: 1
1
1
Contact Maximum Current Rating In Amps
Somas maximum surrent nating in Amps.
7.5 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Material:
Plastic single mating end
Included Contact Quantity:
3 single mating end 1st contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Special Features:
W/2 mtg holes
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0