## NSN 5935-00-553-2620

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-553-2620 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 0.984 inches **Overall Height:** 3.937 inches **Overall Width:** 3.375 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.995 inches and 1.005 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.870 inches and 2.880 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 45 single mating end **Contact Removability:** Nonremovable all mating ends all contact groupings **Contact Maximum Current Rating In Amps:** 30.0 1st mating end 1st contact grouping **Polarization Method:** Polarization boss Shell Type: **Connector Locking Method:** Screw Thready Qty Per Inch (tpi): 12 **Thread Size:** 0.312 inches **Terminal Location:** 

Back all mating ends all contact groupings

**Contact Material:** 

Copper alloy all mating ends all contact groupings

## NSN 5935-00-553-2620

Electrical Receptacle Connector - Page 2 of 2



## **Contact Surface Treatment:** Gold all mating ends all contact groupings and silver all mating ends all contact groupings **Insert Material:** Plastic melamine single mating end and plastic phenolic single mating end **Terminal Type:** Solder well all mating ends all contact groupings **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Type:** Round socket all mating ends all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.090 gold grains, troy and 0.090 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Uns Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No Fiig: A039b0