

View Online at <https://aerobasegroup.com/nsn/5935-00-553-3227>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand and right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

1.070 inches

**Overall Diameter:**

1.000 inches

**Environmental Protection:**

Moisture resistant and vibration resistant

**Threaded Device Type:**

Back shell and coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

14s-5 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

13.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

200.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

250.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Internally threaded coupling nut

**Thread Length:**

0.387 inches and 0.427 inches

**Thread Size:**

0.750 inches and 0.875 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and chromate

**Included Contact Quantity:**

5 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surface silver

**Precious Material And Weight:**

0.005 silver grains, troy

**Precious Material:**

Silver

**Thread Series Designator:**

Unef and unef

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0