Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-553-9424

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
0.766 inches
Overall Diameter:
1.281 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
16-35 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thread Length:
0.219 inches
Thready Qty Per Inch (tpi):
20
Thread Size:
0.9375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:

Crimp single mating end single contact grouping

# NSN 5935-00-553-9424

Electrical Plug Connector - Page 2 of 2



#### Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Nickel

# Included Contact Quantity:

55 single mating end single contact grouping

# Included Contact Type:

Round pin single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

# **Precious Material And Weight:**

0.055 gold grains, troy and 0.055 silver grains, troy

#### **Precious Material:**

Gold and silver

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unef

Specification Data:

81349-mil-c-38999 government specification

# Shelf Life:

N/a

#### Unit Of Measure:

--

#### **Demilitarization:**

No

Fiig:

A039b0