NSN 5935-00-557-1294

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-557-1294

| Thread Class: |
|--|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight shape, internal coupling |
| Overall Length: |
| 5.875 inches |
| Overall Diameter: |
| 2.000 inches |
| Cable Entrance Diameter: |
| 0.200 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Nonstd single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Internally threaded coupling nut |
| Connector Cable Strain Relief Method: |
| Conduit nut |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 53.5 single mating end single contact grouping |
| Thready Qty Per Inch (tpi): |
| 18 |
| Thread Size: |
| 1.875 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| Insert Material: |
| Rubber single mating end |
| Terminal Type: |
| Solder well single mating end single contact grouping |

NSN 5935-00-557-1294Electrical Plug Connector - Page 2 of 2



| Shell Material: |
|--|
| Aluminum alloy |
| Shell Surface Treatment: |
| Anodize |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Included Contact Type: |
| Coaxial socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material And Weight: |
| 0.005 silver grains, troy |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Uns |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |
| No |
| No Fiig: |