## NSN 5935-00-557-2399

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-557-2399 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.018 inches **Overall Height:** Between 1.552 inches and 1.572 inches **Overall Width:** Between 1.552 inches and 1.572 inches **Environmental Protection:** Pressure proof **Unthreaded Mounting Hole Diameter:** Between 0.118 inches and 0.124 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 1.245 inches and 1.255 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 1.245 inches and 1.255 inches **Distance From Mounting Shoulder To Front Face:** Between 0.469 inches and 0.479 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 22-55 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Externally threaded shell

Thread Length: 0.312 inches

## NSN 5935-00-557-2399

Electrical Receptacle Connector - Page 2 of 2



| Thready Qty Per Inch (tpi):   |
|---|
| 4   |
| Thread Size:  |
| 1.375 inches  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Insert Material:  |
| Rubber single mating end  |
| Terminal Type:  |
| Solder well single mating end single contact grouping   |
| Shell Material:   |
| Aluminum alloy  |
| Shell Surface Treatment:  |
| Cadmium and chromate  |
| Included Contact Quantity:  |
| 55 single mating end single contact grouping  |
| Included Contact Type:  |
| Round pin single mating end single contact grouping   |
| Precious Material And Location:   |
| Contact surfaces gold and contact surfaces silver   |
| Precious Material And Weight:   |
| 0.055 gold grains, troy and 0.055 silver grains, troy   |
| Precious Material:  |
| Gold and silver   |
| Thread Series Designator:   |
| Double stub   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
|   |