

View Online at <https://aerobasegroup.com/nsn/5935-00-558-4754>

**Body Style:**

Straight shape

**Overall Length:**

2.450 inches

**Overall Height:**

1.000 inches

**Overall Width:**

0.360 inches

**Environmental Protection:**

Vibration resistant and shock resistant and corrosion resistant and moisture resistant and salt water resistant and heat resistant and cold resistant

**Unthreaded Mounting Hole Diameter:**

1.000 inches

**Distance Between Mounting Facility Centers:**

2.150 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

31 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1, grade b military specification 1st treatment response single mating end single contact grouping

**Terminal Type:**

Wire wrap single mating end single contact grouping

**Contact Material Specification:**

Qq-p-750, composition a federal specification single material response single mating end single contact grouping

**Insert Material Specification:**

Mil-p-19833, type gdi-30 military specification single material response single mating end

**Included Contact Quantity:**

36 single mating end single contact grouping

**Included Contact Type:**

Round socket single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.036 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.