

View Online at <https://aerobasegroup.com/nsn/5935-00-558-8127>

Body Style:

Straight shape

Overall Length:

1.435 inches

Overall Height:

0.415 inches

Overall Width:

0.345 inches

Environmental Protection:

Moisture proof and vibration resistant and salt water resistant

Unthreaded Mounting Hole Diameter:

0.020 inches

Distance Between Mounting Facility Centers:

Between 1.210 inches and 1.220 inches

Mating End Quantity:

1

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.0 single mating end single contact grouping

Polarization Method:

Mating end

Shell Type:

Solid

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Material Specification:

Qq-c-530 federal specification single material response single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-14, type sdc military specification single material response single mating end

Included Contact Quantity:

51 single mating end single contact grouping

Included Contact Type:

Twisted pin single mating end single contact grouping

Special Features:

Insulated wire leads 18.000 in. Lg

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.051 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.