NSN 5935-00-560-3955

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-560-3955

Body Style:		
Straight shape, flange mount, external coupling		
Overall Length:		
0.833 inches		
Overall Height:		
1.141 inches		
Overall Width:		
1.141 inches		
Environmental Protection:		
Moisture proof and vibration resistant		
Unthreaded Mounting Hole Diameter:		
Between 0.115 inches and 0.130 inches		
Center To Center Distance Between Mounting Facilities Parallel To Height:		
0.906 inches		
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:		
0.906 inches		
Distance From Mounting Shoulder To Front Face:		
Between 0.317 inches and 0.322 inches		
Mating End Quantity:		
1		
Contact Removability:		
Nonremovable single mating end single contact grouping		
Polarization Method:		
Key, multiple key groove		
Insert Position In Deg:		
0.0		
Shell Type:		
Potting		
Connector Locking Method:		
Bayonet pin		
Connector Cable Strain Relief Method:		
Potting type		
Terminal Location:		
Back single mating end single contact grouping		
Contact Material:		
Copper alloy single mating end single contact grouping		
Contact Surface Treatment:		
Gold single mating end single contact grouping and silver single mating end single contact grouping		
Terminal Type:		
Solder well single mating end single contact grouping		
Shell Material:		

Aluminum alloy

NSN 5935-00-560-3955

Electrical Receptacle Connector - Page 2 of 2



Included	Contact	Quantity:
----------	---------	-----------

37 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and contact surface silver

Precious Material And Weight:

0.037 gold grains, troy and 0.037 silver grains, troy

Precious Material:

Gold and silver

Test Data Document:

81349-mil-c-27599 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-27599 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0