## NSN 5935-00-563-1173

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-563-1173

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

4.360 inches

**Overall Height:** 

0.755 inches

**Overall Width:** 

Between 0.333 inches and 0.353 inches

**Environmental Protection:** 

Moisture proof and salt water resistant and vibration proof

**Unthreaded Mounting Hole Diameter:** 

Between 0.125 inches and 0.131 inches

**Distance Between Mounting Facility Centers:** 

Between 4.032 inches and 4.040 inches

**Board Accommodated Length:** 

3.588 inches single board and 3.604 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.070 inches

**Mating End Quantity:** 

1

## **Contact Position Arrangement Style:**

1 row of contacts inserted board single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:** 

22 single mating end single contact grouping

**Included Contact Type:** 

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

**Precious Material And Weight:** 

0.022 gold grains, troy

## NSN 5935-00-563-1173

Electrical Receptacle Connector - Page 2 of 2



Gold
Test Data Document:
81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-21097/21a government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

A039b0

Fiig:

Mil-std (military Standard):

Mil-g-45204 spec.

**Precious Material:**