## NSN 5935-00-564-3991

Aluminum alloy

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-564-3991

| ·   |
|---|
| Body Style:   |
| Straight shape, external coupling w/backshell   |
| Overall Length:   |
| 0.692 inches  |
| Overall Height:   |
| 1.234 inches  |
| Overall Width:  |
| 1.234 inches  |
| Environmental Protection:   |
| Moisture proof and salt water resistant and vibration resistant                                     |
| Unthreaded Mounting Hole Diameter:  |
| Between 0.115 inches and 0.130 inches   |
| Center To Center Distance Between Mounting Facilities Parallel To Height:                           |
| 0.069 inches  |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:                         |
| 0.969 inches  |
| Distance From Mounting Shoulder To Front Face:  |
| Between 0.317 inches and 0.322 inches   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 16-8 single mating end  |
| Contact Removability:   |
| Removable single mating end single contact grouping   |
| Polarization Method:  |
| Keyway or multiple keyway   |
| Insert Position In Deg:   |
| 0.0   |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Bayonet pin   |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping and silver single mating end single contact grouping |
| Terminal Type:  |
| Crimp single mating end single contact grouping   |
| Shell Material:   |

## NSN 5935-00-564-3991

Electrical Receptacle Connector - Page 2 of 2



| Shell Surface Treatment:   |
|--|
| Cadmium and chromate   |
| Included Contact Quantity:   |
| 8 single mating end single contact grouping  |
| Included Contact Type:   |
| Round pin single mating end single contact grouping  |
| Precious Material And Location:  |
| Contact surfaces gold and contact surfaces silver  |
| Precious Material And Weight:  |
| 0.008 gold grains, troy and 0.008 silver grains, troy  |
| Precious Material:   |
| Gold and silver  |
| Test Data Document:  |
| 81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-c-38999 government specification   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |

Fiig:

A039b0