## NSN 5935-00-564-4048

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-564-4048
Thread Class:
2a and 2b
Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
2.125 inches
Overall Diameter:
1.594 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Threaded Device Type:
Back shell and coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
22-19 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Thread Length:
0.290 inches and 0.664 inches
Thready Qty Per Inch (tpi):
18 and 18
Thread Size:
1.312 inches and 1.375 inches
Terminal Location:
Back single mating end single contact grouping
Terminal Type:
Crimp single meting and single contact grouping

Crimp single mating end single contact grouping

## **NSN 5935-00-564-4048**Electrical Plug Connector - Page 2 of 2

A039b0



Shell Material:	
Aluminum alloy	
Shell Surface Treatment:	
Cadmium	
Shell Surface Treatment Specification:	
Qq-p-416, type 2, cl 3 federal specification single treatment response	
Included Contact Quantity:	
14 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Test Data Document:	
81349-mil-c-5015 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification	nc
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
Unef and unef	
Specification Data:	
81349-mil-c-5015 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
- <del>-</del>	
Demilitarization:	
No	
Fiig:	