NSN 5935-00-564-4062

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-564-4062 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 0.622 inches **Overall Height:** 0.525 inches **Overall Width:** 0.312 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 36 **Thread Size:** 0.250 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping Solder well single mating end single contact grouping

Contact Surface Treatment: Gold single mating end single contact grouping **Terminal Type: Included Contact Quantity:** 1 single mating end single contact grouping

NSN 5935-00-564-4062

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.001 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No Fiig: A039b0